



NUMERIC MESSAGING
ONE WAY PAGER
NP-88

Great Things Come From Small Packages



Unication Numeric Pager

The NP-88 offers accessibility to stay on top of your busy lifestyle. Perfect for basic wireless communication and user-friendly operation. You can set the pager to generate an audible or a vibration alert no matter under noisy or quiet environments when you are expecting an important page. The NP-88 is compact, lightweight, inexpensive, and the best choice when you need reliable paging with broad coverage.

NUMERIC PAGER

Model Type

NP-88 Numeric Pager POCSAG

Synthesized



FEATURE LIST:

DISPLAY:

- * Backlight
In low-light conditions, the backlight makes the screen easy to read.
- * Standby Screen
The standby screen displays the time of day/date or no display.
- * Time of Day and Day/Month
The time of day and the date display whether the pager is on or off.


INDICATORS/ ALERT:

- * Low Battery Indicator
When battery power reaches low levels, low cell is displayed, prompting you to change the battery. All pager alerts change to two seconds in length.
- * Automatic Alert Reset
The pager alerts automatically stop, even if no buttons are pressed.
- * Personal Alarm
This alarm can be set to alert you. The alarm works even when the pager is off.
- * Reminder Alert
The pager chirps or vibrates every two minutes until you read all unread messages.
- * User Selectable Audible Alerts
A selection of five alert tones give you a choice of message alerts heard when you are paged in the audible alert mode D.

MESSAGING:

- * Duplicate Messages
If the same message is received more than once, duplicate sign is displayed at the beginning of the latest message. This message contains the latest timestamp and prevents a repeated message from taking an extra memory slot.
- * Message Erase
Messages can be erased all at once or selectively at your choice to free space in memory.
- * Memory Retention
All messages remain in memory, even when the pager is off and while the battery is being replaced.
- * Memory Capacity
The NP88 POCSAG pager can store up to sixteen 20-character messages, for a total of 320 characters.
- * Message Protect
You can protect up to eight messages stored in the pager memory.
- * Overflow
Overflow is displayed when more unread messages are received than the available message memory can hold. After you read all of your unread messages, the standby screen is displayed.
- * Timestamp
The time and the date of a message received are displayed on the screen after each message.

For more information, please contact



NP-88

Product Specifications

Band splits	VHF	UHF	900 MHz
Frequency Range	137 – 143MHz 143 – 153MHz 153 – 163MHz 163 – 174MHz	450 – 460MHz 460 – 470MHz	929 – 932MHz
Baud Rate (bps)	512, 1200, 2400 bps		
Code Format	POCSAG CCIR No. 1		
Paging Sensitivity (µV/m) (typical/maximum µV per meter unless otherwise noted):	512.bps: ≤ 5 uV/m 1200.bps: ≤ 7 uV/m 2400.bps: ≤ 10 uV/m	512.bps: ≤ 6 uV/m 1200.bps: ≤ 8 uV/m 2400.bps: ≤ 10 uV/m	512.bps: ≤ 6 uV/m 1200.bps: ≤ 8 uV/m 2400.bps: ≤ 10 uV/m
Selectivity	≥ 60 dB	≥ 55 dB	≥ 50 dB
Frequency Stability	+/- 15 ppm	+/- 5 ppm	+/- 3.5 ppm
Spurious Rejection	≥ 50 dB		40 dB below carrier
Alert Tone	78 dB @ 12 inches (2730 Hz Standard Alert)		
Operating Temperature	5 °C to 40 °C (40 °F to 105 °F)		
Channel Spacing	25 kHz		
Frequency Deviation	+/- 4.5 kHz		
Power Supply	One 1.5V, AAA-size Alkaline Battery		
Battery Life (Based on 2 pages/day; 24 hour ON; full-capacity alkaline battery)	512 Baud: ≈ 25 days 1200 Baud: ≈ 23 days 2400 Baud: ≈ 20 days		
Weight with Battery	60g		
Dimensions	63.65 x45.0 x17.5mm(2.50 x1.77 x0.69in)		



Corporate Headquarters:
Unication Co., Ltd.,
5F., No. 6, Wu-Kung 5Rd., Hsinchuang City,
Taipei, Taiwan. R.O.C.
Phone: + 886 2 2299 9678
Fax: +886 2 2299 7998
Email: salesenquiry@uni.com.tw

Dallas Sales Office:
Unication USA Inc.
1901 E. Lamar Blvd.,
Arlington, TX 76006, U.S.A.
Phone: 817-303-9320
Fax: 817-886-3424
Email: sales@uniamericas.com

www.uni.com.tw